

HPT Steel Matrix

Panel Finishes	Manufacturer	Internal Use	External Use	Steel Substrate *	Paint Thickness μm (nominal)	Laminate Thickness μm (nominal)	Plastisol Thickness μm (nominal)	Coating Warranty (Years)	For Further Information
Foodsafe Laminate	Tata® Advantica© L Control	✓	-	0.5mm Z225 HDG	-	120	-	Project Specific	www.tatasteelconstruction.com
Foodsafe Polyester	Tata® Advantica© GMS5880	✓	-	0.5mm Z225 HDG	25	-	-	Project Specific	www.tatasteelconstruction.com
Primer/Liner	Various	✓	-	0.5mm Z225 HDG	7-10	-	-	Project Specific	Various - Consult HPT
PET	Tata® Advantica© CL Clean	✓	-	0.5mm Z100 HDG	35	20 (55 Ovr)	-	-	-
Prisma	Colorcoat Prisma	✓	✓	0.5mm Galvalloy	50	-	-	30 **	www.colorcoat-online.com
Ultra	HPS200 Ultra	✓	✓	0.5mm Galvalloy	200	-	200	40 **	www.colorcoat-online.com
Leathergrain	Colorcoat LG	✓	✓	0.5mm Z275 HDG	200	-	200	25 **	www.colorcoat-online.com
PVDF	Various	✓	✓	0.5mm	27	-	-	10 **	Various - Consult HPT
Architectural Polyester	Various	✓	✓	0.5mm	25	-	-	-	Various - Consult HPT

* For alternative steel thickness available please consult HPT.

** Please refer to steel manufacturer for detailed information.